# **SA Performer series**

## Reinforcement Loudspeaker

#### SA 4826 full range cabinet

The SA 4826 is a compact, high-power full range cabinet capable of producing high sound pressure levels with very low distortion. This is achieved by using two SA 1202 12" low-mid drivers and the SA 8526 Compact Driver.

# SA 4826 full range cabinet

### **Technical Specifications**

#### Available options:

- Flightcased version;
- Dolly for transportation including castors;
- Tube stand adaptor for Performer series subwoofer cabinets;
- Rigging system.

Each of these options may be ordered seperately.



Physical dimensions of the SA 4826; flightcased version. The protective cover/dolly for transportation is shown at the right side.

- High acoustic output
- Compact rugged design
- Equipped with two SA 1202 high efficiency drivers and the SA 8526 Compact Driver
- Unequalled transient response
- Road-proof in cased version
- Prepared for use with the SA 4816 subwoofer through position plates (cased version)

**E** ®

stage accompany

# **SA Performer series**

# **Reinforcement Loudspeaker**

### **Technical specifications**

Frequency response: Driver complement:

Nominal impedance:

Low-mid sensitivity: High sensitivity: Low-mid max. RMS power: High max. RMS power: Low-mid max. peak power: High max. peak power: Enclosure: 80 Hz - 32 kHz +/- 3 dB Two SA 1202 LF drivers; One SA 8526 Compact Driver 4 Ohms LF driver (parallel) 5 Ohms HF driver 101 dB, @ 1 W 1 meter 99 dB, @ 1 W 1 meter 300 Watts 120 Watts 2000 Watts (200 ms) 1000 Watts (200 ms) Vented, multi-ply birchwood

# SA 4826 full range cabinet

### **Technical Specifications**

Finish: Physical overall dimensions: Flightcased version: Including castors: Weight:

Protective grill: Connector: Rigging (optional): Blue, other colours on request 1008 x 380 x 450 mm 1013 x 385 x 455 mm add 130 mm to depth 55 kg

+ 5 kg for flightware

+ 8 kg for dolly with castors+ 5 kg for flyer system

Expanded metal screen Neutrik 8 pin Speakon Aircraft snap-lock strips



Physical dimensions of the SA 4826; normal version. The protective cover/dolly for transportation is shown at the right side.



Stage Accompany B.V. Anodeweg 4 1627 LJ Hoorn The Netherlands Phone: (0)2290 - 12542 Fax: (0)2290 - 11192 Telex: 37989 stage nl